Round Smooth Pole Base PRODUCTION FORM

MANUFACTURER:				SALES ORDER:			
PHONE #:					P.O. NO.:		
EMAIL:					DATE:		
CUSTOMER:			JOI	B/LOCATION NAME:			
BASE DIAMETER:	DESIGN	BY OTHERS		ANCHOR BOLTS		PRO	BOLT JECTION
BASE LENGTH:					Tell Control of the C	a	+
HORZ. BARS (SIZE	& SPACING):			PVC ELEC_CONDUITS			
VERT. BARS (QTY.	& LENGTH):			-	A		
BOLT CIRCLE:				STEEL REINFORCING	7		
BOLT PROJECTIO	N:			_		√ ✓ :	
SIZE OF BOLTS:				-		√. · ∠ · ·	
WEIGHT:				-		I III	
			NOTE: 1.) DESIGN BY OTHERS	.		T DEF	
SIZE	ANGLE	DEPTH (FROM TOP OF BASE)	2.) GRADE 60 REBAR 3.) F'c = 5000 PSI		A A A	CONDUIT DEPTH	
					4	S	LENGTH
						A	FEN
					A 4	4 4	
					7		
	O° BO	IT.		HAMFERED	4 4	A	
	CIR	LT CCLE		OP EDGE	A A	A A	+
270° (°) 90° CHAI				HAMFERED		4	
\\ \&				OINT	A	· 4	
	180°						
Reference only - see table for actual location							
				7	DIAMETER	<u>:</u>	

CUSTOMER APPROVAL

SIGNATURE: PRINT NAME:

This drawing and all information on it supersedes any other information received or provided by customer and/or supplier of light pole.