




Typical XL Gravity Wall Section



This drawing is for reference only. Determination of the suitability and/or manner of use of any details contained in this document is the sole responsibility of the design engineer of record. Final project designs, including all construction details, shall be prepared by a licensed professional engineer using the actual conditions of the proposed site.

DRAWN BY:	NWL	TITLE: <h3 style="text-align: center;">Typical Redi-Rock XL Block Wall Section</h3>	 <p>05481 US 31 SOUTH, CHARLEVOIX, MI 49720 (866) 222-8400 ext 3010 • engineering@redi-rock.com www.redi-rock.com</p>
APPROVED BY:	JRJ		
DATE:	20APR2018		
SHEET:	1 of 1		
		FILE:	Typical XL Section 041318.dwg


Typical Gravity Wall Section



This drawing is for reference only. Determination of the suitability and/or manner of use of any details contained in this document is the sole responsibility of the design engineer of record. Final project designs, including all construction details, shall be prepared by a licensed professional engineer using the actual conditions of the proposed site.

DRAWN BY:	JRJ	TITLE: <h1 style="text-align: center;">Typical Gravity Wall Detail</h1>	 <p>05481 US 31 SOUTH, CHARLEVOIX, MI 49720 (866) 222-8400 ext 3010 • engineering@redi-rock.com www.redi-rock.com</p>
APPROVED BY:	JRJ		
DATE:	17MAR2016		
SHEET:	1 of 1		
FILE:		1 Typical Gravity Wall Detail 031716.dwg	

Typical Gravity Wall Section with Hollow-Core Blocks




Note: Wall designs typically include a combination of solid, PC, and hollow-core blocks. Redi-Rock blocks are designed to be used together. Block type, size, and configuration will vary based on site-specific conditions and wall height.

This drawing is for reference only. Determination of the suitability and/or manner of use of any details contained in this document is the sole responsibility of the design engineer of record. Final project designs, including all construction details, shall be prepared by a licensed professional engineer using the actual conditions of the proposed site.

DRAWN BY:	NWL	Typical Gravity Wall Detail with Hollow-Core Blocks	
APPROVED BY:	NWL		
DATE:	08JAN2020		
SHEET:	1 of 1		
		FILE: Typical HC Wall Section 010820.dwg	05481 US 31 SOUTH, CHARLEVOIX, MI 49720 (866) 222-8400 ext 3010 • engineering@redi-rock.com www.redi-rock.com

Sample Plan and Profile Gravity Wall



LEGEND:


BLOCK SERIES (RETAINING, FREESTANDING, ACCESSORY)

BLOCK SIZE (28, 41, & 60)

R-41M BLOCK TYPE (BOTTOM, MIDDLE, TOP or CORNER GARDEN)

GRADE DROPS ALONG EXPOSED TEXTURED SIDE OF CORNER GARDEN BLOCK (TYPICAL)

PROPOSED FINISH GRADE AT TOP OF WALL




- This drawing is for reference only.
- **Final designs for construction must be prepared by a registered Professional Engineer** using the actual conditions of the proposed site.
- **Final wall design must address both internal and external drainage and shall be evaluated by the Professional Engineer who is responsible for the wall design.**

DRAWN BY: JRJ
APPROVED BY: JRJ
DATE: 22MAR2016
SHEET: 1 of 1

TITLE: Sample Plan and Profile Gravity Wall
FILE: 2 Sample Plan and Profile Gravity Wall 032216.dwg

REDI-ROCK
05481 US 31 SOUTH, CHARLEVOIX, MI 49720
(866) 222-8400 ext 3010 • engineering@redi-rock.com
www.redi-rock.com




This drawing is for reference only. Determination of the suitability and/or manner of use of any details contained in this document is the sole responsibility of the design engineer of record. Final project designs, including all construction details, shall be prepared by a licensed professional engineer using the actual conditions of the proposed site. Final wall design must address both internal and external drainage and all modes of wall stability.

DRAWN BY: B. Lindfors	TITLE:	Large Batter Wall Section REDI-ROCK® 05481 US 31 SOUTH, CHARLEVOIX, MI 49720 (866) 222-8400 ext 3010 • engineering@redi-rock.com www.redi-rock.com
APPROVED BY: J. Johnson		
DATE: Jan 28, 2016		
SHEET: 1 of 1	FILE: Large Batter Gravity Wall Section 012816.dwg	

BLOCK-TO-BLOCK SETBACK OPTIONS


NO SCALE

Five degree (5°) setback (Standard)



Setback = $1 \frac{5}{8}$ " (41 mm)
(5° batter angle on wall)


Move blocks forward during
installtion to engage shear
knobs (Typical)



Available with:


- 28" (710 mm) blocks, 41" (1030 mm) blocks, and 60" (1520 mm) blocks
- 28" (710 mm) PC blocks (shown here) and 41" (1030 mm) PC blocks

One degree (1°) setback (Specialty)



Setback = $\frac{3}{8}$ " (10 mm)
(1° batter angle on wall)


Move blocks forward during
installtion to engage shear
knobs (Typical)



Available with:


- 28" (710 mm) blocks, 41" (1030 mm) blocks, and 60" (1520 mm) blocks
- 28" (710 mm) PC blocks (shown here) and 41" (1030 mm) PC blocks

Zero (0°) setback (Specialty)



Setback = 0" (0 mm)
(0° batter angle on wall)

Move blocks forward during
installtion to engage shear
knobs (Typical)



Available with:

- 28" (710 mm) blocks, 41" (1030 mm) blocks, and 60" (1520 mm) blocks
- 28" (710 mm) PC blocks (shown here) and 41" (1030 mm) PC blocks

The block-to-block setback available with Redi-Rock is controlled by the size and location of the shear knobs (domes) cast into the blocks. While the 10" (254 mm) diameter knob and the $1 \frac{5}{8}$ " (41 mm) setback position is the most common configuration, Redi-Rock has three different knob sizes and three different locations available.

DRAWN BY: JRJ
APPROVED BY: JRJ
DATE: 06-22-2015
SHEET: 1 of 1

TITLE:

Block Setback Options Normal Batter

FILE: 4 Block Setback Options Normal Batter 062215.dwg


REDI-ROCK®
05481 US 31 SOUTH, CHARLEVOIX, MI 49720
(866) 222-8400 ext 3010 • engineering@redi-rock.com
www.redi-rock.com

BLOCK-TO-BLOCK SETBACK OPTIONS

NO SCALE

9" (230 mm) Setback


Blocks




Available with:

- 41" (1030 mm) blocks (shown here) and 60" (1520 mm) blocks
- Not available in PC blocks

Setback = 9 3/8" (238 mm)
(27.5° batter angle on wall)




Planter Blocks



Available with:

- 41" (1030 mm) blocks (shown here) and 60" (1520 mm) blocks
- Not available in PC blocks

Setback = 16 5/8" (422 mm)
(43° batter angle on wall)



Redi-Rock has two options for large batter retaining walls. Both options are created by relocating the knob so that it is further back in the Redi-Rock blocks compared to our smaller batter walls (5° and less). There are two knob locations further back in the block which create the 9" (230 mm) setback block and the planter block. Blocks made with knobs in either of these locations almost exclusively use 10" (254 mm) diameter knobs.

DRAWN BY:	JRJ
UPDATED BY:	DLH
DATE:	01-03-2022
SHEET:	1 of 1

TITLE:


Block Setback Options Large Batter

FILE: Block Setback Options Large Batter 010322.dwg

REDI-ROCK


05481 US 31 SOUTH, CHARLEVOIX, MI 49720
(866) 222-8400 ext 3010 • engineering@redi-rock.com
www.redi-rock.com

The Redi-Rock retaining blocks are available with multiple shear knob size and location options, to permit wall batter design flexibility. This detail depicts alternating $16\frac{5}{8}"$ (422 mm) Planter and $1\frac{5}{8}"$ (41 mm) Standard setback blocks, however designs are possible using more than one Standard setback block between Planter blocks. The regular repetition of combinations of different setback blocks within a wall profile can have structural and aesthetic significance. Abrupt changes in wall batter that carry over multiple blocks are not recommended.



This drawing is for reference only. Determination of the suitability and/or manner of use of any details contained in this document is the sole responsibility of the design engineer of record. Final project designs, including all construction details, shall be prepared by a licensed professional engineer using the actual conditions of the proposed site. Final wall design must address both internal and external drainage and all modes of wall stability.

DRAWN BY: B. Lindfors	TITLE: Alternating Planter & Standard Batter Block Wall Section	REDI-ROCK® 05481 US 31 SOUTH, CHARLEVOIX, MI 49720 (866) 222-8400 ext 3010 • engineering@redi-rock.com www.redi-rock.com
APPROVED BY: J. Johnson		
DATE: Jan 28, 2016		
SHEET: 1 of 1	FILE: Alt Planter & Standard Batter Wall Section 012816.dwg	



This drawing is for reference only. Determination of the suitability and/or manner of use of any details contained in this document is the sole responsibility of the design engineer of record. Final project designs, including all construction details, shall be prepared by a licensed professional engineer using the actual conditions of the proposed site.

The guidance provided is based upon generally accepted engineering principles, and should be considered a "rule of thumb." It should be noted that toe slopes generally decrease global stability and bearing capacity. These should be checked and verified by the responsible party.

DRAWN BY:	DLH	TITLE:	Typical Toe Slope Detail
APPROVED BY:	NWL		
DATE:	5/28/2021		
SHEET:	1 of 1	FILE:	
			REDI-ROCK® 05481 US 31 SOUTH, CHARLEVOIX, MI 49720 (866) 222-8400 ext 3010 • engineering@redi-rock.com www.redi-rock.com