Stepped 9" (230 mm) Setback Wall with Aligned Base Garden Corner block (Typical) Optional field trimming as shown Corner block (Typical) Top block (Typical) Grade line (Bottom of wall aligned) Bottom block with 10" (254 mm) diameter knobs in the 9" (230 mm) setback position (Typical) Bottom block with 6 3/4" (171 mm) diameter knobs in the zero setback position (Typical) Parallel Setback Middle block with 10" (254 mm) diameter knobs in the 9" (230 mm) setback position (Typical) Zero setback bottom block as needed to maintain minimum bury Grade line (Bottom of wall aligned) This drawing shows typical installation details required for setback walls with the bottom of the wall aligned. Specific block placement will vary depending on site grades. **Opposed Setback**

This drawing is for reference only. Determination of the suitability and/or manner of use of any details contained in this document is the sole responsibility of the design engineer of record. Final project designs, including all construction details, shall be prepared by a licensed professional engineer using the actual conditions of the proposed site.

DRAWN BY:	JRJ	Stepped 9" Setback Wall with Aligned Base
APPROVED BY:	JRJ	
DATE:	06-22-2015	
SHEET:	1 of 1	FILE: 3 Stepped 9" Setback Wall with Aligned Base 062215.dwg

