

90 DEGREE OUTSIDE CORNER

NOTE: ANY COMBINATION OF GRAND LEDGE FREESTANDING BLOCKS A, B, C, D, E, AND F CAN BE USED FOR THE CONSTRUCTION OF TYPICAL OUTSIDE CORNERS. PATTERN SHOWN UTILIZES B, C, E, AND F FREESTANDING BLOCKS. FOR WALLS ABUTTING VERTICAL CONSTRAINTS ON EITHER SIDE OF THE CORNER AND FOR DOUBLE OUTSIDE 90° CORNERS, A DIFFERENT CONFIGURATION IS REQUIRED TO LIMIT CUTTING OF BLOCKS.

This drawing is for reference only. Determination of the suitability and/or manner of use of any details contained in this document is the sole responsibility of the design engineer of record. Final project designs, including all construction details, internal and external stability, and drainage, shall be prepared by a licensed professional engineer using the actual conditions of the proposed site.

DRAWN BY: T. GRUENEWALD	TITLE:
APPROVED BY: L. HELBLING	GRAND LEDGE 90 DEGREE OUTSIDE CORNER
DATE: MAY 15, 2024	90 DEGREE OUTSIDE CORNER
SHEET NO.:	DRAWING FILE:
1 of 1	Grand Ledge_90 Deg Outside Corner_05152024.dwg

