



MINIMUM ADDITIONAL BURY DEPTH

RUN OF SLOPE, s (ft)	ADDITIONAL BURY DEPTH (ft)	ADDITIONAL BURY DEPTH (mm)
10	0'-5"	120
8	0'-6"	150
6	0'-8"	200
4	1'-0"	300
3	1'-4"	400
2.5	1'-7"	500
2	2'-0"	600

- Block sizes and placement shown are for reference only. Individual Rosetta blocks will vary with installation pattern.
- Final wall design must address both internal and external drainage and shall be evaluated by the Professional Engineer who is responsible for the wall design.

This drawing is for reference only. Determination of the suitability and/or manner of use of any details contained in this document is the sole responsibility of the design engineer of record. Final project designs, including all construction details, shall be prepared by a licensed professional engineer using the actual conditions of the proposed site.

DRAWN BY: DLH
 APPROVED BY: DLH
 DATE: 11/02/2020
 SHEET NO.: 1 of 1

TITLE:
 TYPICAL TOE SLOPE DETAIL
 DRAWING FILE:
 Typical Toe Slope Detail 110220.dwg

ROSETTA
 HARDSCAPES, LLC
 05481 US 31 SOUTH CHARLEVOIX, MI 49720
 877-777-6558 • 231-237-9656 Fax • www.discoverrosetta.com